

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Special stamping ink R 9  
dark blue (15035000046038)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

Industrial marking ink

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Stefan Kupietz GmbH & Co. KG  
Chemische Fabrik

**Street :** August-Wilhelm-Kühnholz-Str. 9

**Postal code/city :** 26135 Oldenburg

**Telephone :** +49(0)441/20 69 50

**Telefax :** +49(0)441 /20 69 520

**Information contact :** E-Mail: info@kupietz.de

### 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Repr. 1B ; H360 - Reproductive toxicity : Category 1B ; May damage fertility or the unborn child.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3

**Hazard statements**

H226 Flammable liquid and vapour.

H360 May damage fertility or the unborn child.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

(2-METHOXYMETHYLETHOXY)PROPANOL ; EC No. : 252-104-2; CAS No. : 34590-94-8

Weight fraction : < 55 %  
Classification 1272/2008 [CLP] : Substance with a common (EC) occupational exposure limit value.

1-METHOXY-2-PROPANOL ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : < 30 %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

C.I. Basic Blue 7 derivate ; REACH registration No. : 01-2119849083-38-0000

Weight fraction : < 10 %  
Classification 1272/2008 [CLP] : None

C.I. Solvent blue 70 ; EC No. : 304-661-9; CAS No. : 94277-77-7

Weight fraction : < 2,5 %  
Classification 1272/2008 [CLP] : Aquatic Chronic 3 ; H412

C.I. SOLVENT BLACK 29 ; EC No. : 403-720-7; CAS No. : 117527-94-3

Weight fraction : < 1 %  
Classification 1272/2008 [CLP] : Repr. 1B ; H360 Aquatic Chronic 2 ; H411

Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; EC No. : 247-906-4; CAS No. : 26694-69-9

Weight fraction : < 0,5 %  
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Immediately remove all contaminated clothing.

#### Following inhalation

Provide fresh air.

#### In case of skin contact

Wash away with soap and water and rinse.

#### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

## After ingestion

Drink plenty of water.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO<sub>2</sub>) , Extinguishing powder or Water spray jet .

### 5.2 Special hazards arising from the substance or mixture

None

### 5.3 Advice for firefighters

None

### 5.4 Additional information

Cool endangered containers with water in case of fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

### 6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Remove mechanically, take-up residues with absorbing material.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

#### Protective measures

##### Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition. - No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

#### Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

**Storage class :** 3

**Storage class (TRGS 510) :** 3

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

### Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 310 mg/m<sup>3</sup>

Peak limitation : 1(I)

Version : 06.11.2015

Limit value type (country of origin) : TWA ( EC )

Limit value : 50 ppm / 308 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 100 ppm / 370 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

Version : 06.11.2015

Limit value type (country of origin) : STEL ( EC )

Limit value : 150 ppm / 568 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )

Limit value : 100 ppm / 375 mg/m<sup>3</sup>

Remark : H

Version : 08.06.2000

### 8.2 Exposure controls

#### Personal protection equipment

##### Eye/face protection

Use tightly fitting safety glasses.

##### Skin protection

###### Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

##### Respiratory protection

###### Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

#### General health and safety measures

The usual precautionary measures for the handling of chemicals have to be observed.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

**Colour :** dark blue

**Odour :** characteristic

## Safety relevant basis data

<b>Physical state :</b>				liquid	
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	approx.	138	°C	
<b>Flash point :</b>		approx.	46	°C	Brookfield
<b>Vapour pressure :</b>	( 50 °C )	<	1100	hPa	
<b>Density :</b>	( 20 °C )	approx.	0,968	g/cm <sup>3</sup>	
<b>Solvent separation test :</b>	( 20 °C )	<	3	%	
<b>pH :</b>		approx.	4,2		
<b>Flow time :</b>	( 20 °C )	approx.	12	s	DIN-cup 4 mm

## 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

No information available.

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

None, if handled according to order.

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO<sub>2</sub> released. Formation of hydrogen by acids, lyes, moisture possible.

### 10.6 Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter : LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 5660 mg/kg

##### Acute dermal toxicity

Parameter : LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 9999,99 mg/kg

##### Acute inhalation toxicity

##### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

## Irritant and corrosive effects

### Primary irritation to the skin

Parameter : Primary irritation to the skin ( C.I. Solvent blue 70 ; CAS No. : 94277-77-7 )  
Species : Rabbit  
Result : No erythema (redness).  
Parameter : Primary irritation to the skin ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Rabbit  
Method : OECD 404  
Parameter : Primary irritation to the skin ( Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9 )  
Species : Guinea pig  
Method : OECD 404

### Irritation to eyes

Parameter : Irritation to eyes ( C.I. Solvent blue 70 ; CAS No. : 94277-77-7 )  
Species : Rabbit  
Result : No conjunctival redness.  
Parameter : Irritation to eyes ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Rabbit  
Method : OECD 404  
Parameter : Irritation to eyes ( Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9 )  
Species : Rabbit

## Sensitisation

### In case of skin contact

Parameter : Skin sensitisation ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Guinea pig  
Method : OECD 406

### In case of inhalation

Parameter : Sensitisation to the respiratory tract ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Guinea pig  
Method : OECD 406

## STOT-repeated exposure

### STOT RE 1 and 2

Parameter : STOT RE 1 and 2 ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Exposure route : STOT RE 1 and 2  
Test result : STOT RE 1 and 2  
Source : STOT RE 1 and 2

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( C.I. Solvent blue 70 ; CAS No. : 94277-77-7 )  
Species : Brachydanio rerio (zebra-fish)  
Effective dose : 10 - 100 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Cyprinus carpio (Common Carp)  
Effective dose : 1 - 10 mg/l  
Exposure time : 96 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

## Acute (short-term) daphnia toxicity

Parameter : EC50 ( C.I. Solvent blue 70 ; CAS No. : 94277-77-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 65,3 mg/l  
Exposure time : 48 h  
Parameter : EC50 ( Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 1,8 mg/l  
Exposure time : 48 h  
Method : OECD 202

## Acute (short-term) algae toxicity

Parameter : EC50 ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Scenedesmus subspicatus  
Effective dose : > 100 mg/l  
Exposure time : 72 h  
Parameter : EC0 ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Species : Daphnia magna (Big water flea)  
Effective dose : > 1000 mg/l  
Exposure time : 24 h  
Method : OECD 201  
Parameter : EC50 ( Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9 )  
Species : Pseudokirchneriella subcapitata  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 1,4 mg/l  
Exposure time : 72 h  
Method : OECD 201

## Effects in sewage plants

Parameter : EC20 ( C.I. Solvent blue 70 ; CAS No. : 94277-77-7 )  
Inoculum : Activated sludge  
Evaluation parameter : Effects in sewage plants  
Effective dose : > 1000 mg/l  
Exposure time : 0,5 h  
Evaluation : Depending on local conditions and existing concentrations, in the case of discharge in biological sewage plants, problems in the decomposition activity of activated sludge are possible.  
Method : OECD 209  
Source : Effects in sewage plants  
Parameter : EC50 ( C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3 )  
Inoculum : Activated sludge  
Effective dose : > 100 mg/l  
Exposure time : 3 h  
Method : ISO 8192

## 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

### Biodegradation

Parameter : Biodegradation ( Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9 )  
Inoculum : Degree of elimination  
Evaluation parameter : Biodegradation  
Effective dose : 27 %  
Exposure time : 28 t/a  
Method : OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

## 12.3 Bioaccumulative potential

No information available.

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

No information available.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

Do not empty into waters or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation.

#### Product/Packaging disposal

**Waste codes/waste designations according to EWC/AVV**

- 080111

#### Waste treatment options

##### Appropriate disposal / Package

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT RELATED MATERIAL

#### Sea transport (IMDG)

PAINT RELATED MATERIAL

#### Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** D/E  
**Special provisions :** 640E · LQ 5 I · E 1  
**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3  
**EmS-No. :** F-E / S-E  
**Special provisions :** LQ 5 I · E 1  
**Hazard label(s) :** 3



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

#### Air transport (ICAO-TI / IATA-DGR)

**Class(es) :** 3  
**Special provisions :** E 1  
**Hazard label(s) :** 3

#### 14.4 Packing group

III

#### 14.5 Environmental hazards

**Land transport (ADR/RID) :** No  
**Sea transport (IMDG) :** No  
**Air transport (ICAO-TI / IATA-DGR) :** No

#### 14.6 Special precautions for user

None

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations

##### Water hazard class (WGK)

Class : 3 (Strongly hazardous to water) Classification according to VwVwS

#### 15.2 Chemical safety assessment

No information available.

### SECTION 16: Other information

#### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 03. Hazardous ingredients

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

#### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

#### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### 16.6 Training advice

None

#### 16.7 Additional information

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Special stamping ink R 9  
dark blue  
**Revision date :** 02.02.2017  
**Print date :** 02.02.2017

**Version (Revision) :** 17.0.0 (16.0.0)

---

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---